Project Management & Construction Division

Pavement Management Program Maintenance & Rehabilitation



Rick Boeger

Pavement Management Program Supervisor

Pavement Management Program

- MCDOT has operated Pavement Management Database since 1980's
- MCDOT utilized Pavement Preservation Program starting in 2008
- It is a systematic process to plan pavement preservation activities
- It provides, analyzes and summarizes roadway and pavement information
- Identifies optimum strategies, selects cost-effective preservation methods
 - Create roadway statistical reports

Pavement Evaluation


- 1200 miles of Arterial road evaluation annually for Pavement Condition Rating (PCR) and International Roughness Index (IRI)
- 800 miles total of Local road PCR evaluation, 400 miles per year
- Nine Distress criteria are evaluated for extent and severity; transverse, longitudinal, block and fatigue cracks, raveling, rutting, IRI, patching and excess asphalt

Pavement Management Program

							SURFACE DIST 100 POINT SYS						
				DEDU	CIIO	N9 -	TOU POINT STS				and the state	_	
	Trans	verse (LO	ngitudi			110.00	
Extent Spacing	\vdash	Beverity/Width				Extent		-	Severity/Width			101	
> 50 ft	< 3/8"				> 3/8"		Centerline Single	-	+ -	< 3/8'	23	> 3/8"	
> 50 ft 12 ft to 50 ft			(3)	- 4				Wheel Path Single		_	3)	4 5	(6)
12πτο 50 π < 12 ft			(5) (7)	6		(8) 10)T	Multiples	e	2	_	5	8	(8) (10)T
* 12 R	-	2	<u>vo</u> 1	0	1.1	D-76	Multiples		1 3	1.1	7)	0	D-7
	P.o.M.		all fair as			D-70		_	Et a sta	Contract			D-7
	Fatigue Cracking Severity/Width				Block Cracks Severity/Width								
Extent	< 1/8			1/8"		cks	Extent Block S	ize					3/8"
One or two < 50 sf	ΗŤ	(4)	15	(5)	9	(9)	> 60 st		+ 1		(3)	4	(6)
Three or more < 50	2		-	(9)			50 to 6 sf	_		-	(3)		
sf		(6)	6	(7)	10	(11		_	2		(5)	5	(8)
One of two > 50 sf	3	(8)	7	(12	11	(14	< 6 sf	_	3	P	(7)	6	(10)
Three or more > 50 sf	4	(10)	8	(13	12	(15)T							
	0 - XV			100	· · · · ·	D-40							D-5
Rutting						Rav	eling						
Extent				Severi	everity		Extent				Severit		
	aser Average 0.00-0.12		0		(0)	b - 3						Aajor	
Laser Average 0.13-0.25			1		(4)		Wheel Paths < 50% length			1	(2)	5	(3
Laser Average 0.26-0.38			2		(8)		Wheel Paths > 50% length			2	(4)	6	(5
Laser Average 0.39-0.50			3		(12)		Entire Width < 50 length	%		3	(6)	7	(9
Laser Average > 0.50	0		4		(15)	T	Entire Width > 50% length			4	(8)	8	(1
				-		D-60		_	_		-	-	D-6
SI	hoving	j/Pushi	naiCo	r.				_	Pate	:hing			_
Extent	T			verity				Severity/Quality of Repair			pair		
Laser Avg. IRI 0-	+			1	200	1. C	Extent/Number				Poor		
69			1	_	(0)	8	0525555566515555				Par		Poor
Laser Avg. IRI 60- 94		- 3			(3)	i j	< 5 Repairs	1 (01)		4	(04)	7	(07)
Laser Avg. IRI 95- 170	2			(5)		5 to 15 Repairs	12	(02)	5	(05)	8	(09)	
Laser Avg. IRI 171+ 220	3			(8)		> 15 Repairs	49	(03)	6	(06)	9	(10)	
LaserAvg. IRI ≥ 220	4			(10)T							1.1	17	
						D-60		_					D-5
	Exc	ess As		and the second									
Extent	Severity/Film Thin T			film Thic	*								
Wheel Paths < 50% length		1	(3	9	5	(4)							
Wheel Paths > 50% length	s > 50% 2 (5) 6			(6)	Notes: 1. All numbers in parentheses are deduction points.								
Entire Width < 50% k	ength	3	0		7	(8)	2. D = Default.						
Entire Width > 50% I		4	(\$	1)	8	(10)T	 Trigger is activated when the rating is applied if the value results in a lower Pavement Condition Rating (P 						
		D-60				than the sum total	of	the ded	action		11-11-201	 Contract 	



Pavement Preservation Strategies




Pavement Preservation Plan FY2011

Preservation	Quantity (LM)	Cost (\$K)	Unit Cost (\$/SY)
Crack Seal	391	\$2,086	\$0.65
Mill & Resurface, SC/SCW	171	\$11,817	\$8.39
Preservative Seal	205	\$1,488	\$0.88
RBST HV	128	\$2,104	\$2.00
RBST LV	33	\$533	\$2.00
Slurry Seal	48	\$879	\$2.25
AR Overlay	28	\$2,020	\$9.75
ARRA AR Overlay	118	\$7,521	\$7.75
Rehabilitation	2	\$525	\$25.35
Totals:	1124	\$28,973	

Pavement Preservation Completed FY2011


Preservation	Quantity (LM)	Cost (\$K)	Unit Cost (\$/SY)
Crack Seal	415	\$1,313	\$0.39
Mill & Resurface, SC/SCW	154	\$11,558	\$9.13
Preservative Seal	203	\$1,238	\$0.74
RBST HV	121	\$2,692	\$2.72
RBST LV	23	\$461	\$2.50
Slurry Seal	42	\$696	\$2.04
AR Overlay	151	\$10,020	\$8.08
Rehabilitation	4	\$1,367	\$43.87
Totals:	1113	\$29,345	

FY 2011 Completed Maintenance Mileage




Surface Treatments


FY 2011 Actual Maintenance Costs



Surface Treatments

Percent of MCDOT Roadway Rated Excellent and Very Good Pavement Condition Rating (PCR) Higher Than 70





Percent of MCDOT Roadway Smoothness Rated Average to Very Smooth International Roughness Index Rating (IRI) Lower Than 170

Fiscal Year


Pavement Smoothness

- MCDOT goal is to provide smoother, longer lasting, safer and more cost effective pavements
- MCDOT has used a Smoothness specification since 2000
- The Specification has an incentive for excellent paving and a penalty for poor paving
- Smoother pavement correlates to a more comfortable ride with less noise and vibration
- Improved fuel efficiency and reduced vehicle wear and tear
- Smoother roads require less maintenance and last longer
- In 2005 MCDOT won the AQA Showcase in Excellence Award for "Asphalt Pavement Smoothness"

Pavement Preservation Plan for FY2012

Preservation	Quantity (LM)	Cost (\$K)	Unit Cost (\$/SY)
HIP 99 ^h Ave & Del Webb*	40	\$3,270	\$10.00
Mill & Resurface, SCW*	10	\$1,100	\$8.5
RBST HV	100	\$2,050	\$2.50
RBST LV	37	\$762	\$2.50
Slurry Seal	46	\$855	\$2.25
Slurry Seal-Sun Valley Pk*	134	\$3,302	\$3.00
AR Overlay SCW Arterial*	71+28	\$4,927	\$8.50
AR Overlay Usery Pass*	14	\$2,000	\$15.00
Crack Seal	361	\$1,926	\$0.65
Preservative Seal	134	\$827	\$0.75
Recon Desert Sage Subd.*	12	\$1,750	\$17.00
* TIP funded	987	\$22,769	

Yearly Pavement Management Program - Timeline



Annual Report-FY 2011

Preventive Maintenance Performance

Preventive maintenance extends the life of the pavement and provides for better performance. The majority of treatments for flexible pavements involves sealing the existing surface and providing a new wearing surface for traffic. Two of the primary factors leading to the deterioration and premature failure of flexible pavements are oxidization and water environmental damage.

MCDOT has used preventive maintenance practices for decades with excellent results. Table 1 shows the break down of each treatment that is typically used, the frequency of application and the observed increase in pavement life per application.

Treatment	Pavement age at time of first application (yr.)	Frequency of application (yr.)	Observed increase in pavement life (yr.)
Fog Seal/ Rejuvenate	3 to 4	3 to 4	3 to 4
Crack Filling/Sealing	8 to 10	4 to 5	4 to 5
Single Chip Seal	10 to 12	5 to 6	5 to 6
Double Chip Seal	10 to 12	5 to 6	5 to 6
Micro Surfacing	10 to 12	5 10 6	5 to 6
Slurry Seal	10 to 12	5 to 6	5 to 6
Arterial—Thin Overlay— 1.5"- 2" ARHM Local—Mill & Resurface 1.5" ARHM * TBD—To be determined	12 to 15 35+	12 to 15 TBD*	12+ TBD*

Table 1: Preventive Maintenance Treatment Longevity

Pavement Management Program

Pavement Preservation Plans

- Fog Seal / Preservative Seal
- Crack Fill
- Chip Seals
- Slurry Seal
- AR Overlay Arterials
- Mill and Resurface Locals
- Rehabilitation Locals





















LV Chip Seal ¼" Aggregate



HV Chip Seal 3/8" Aggregate


















manna manana

mmon

06/07/2010 02:31



















Thank You! Questions?